

BASF SE

ENGINEERING PLASTICS EUROPE, E-KTE/MP - F206, LUDWIGSHAFEN 67056 DE

GP-22

Acrylonitrile Butadiene Styrene (ABS), "Terluran", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	
ALL	0.8	HB	3	1	90	80	95	
	1.5	HB	3	1	90	80	95	
	3.0	HB	3	0	90	80	95	
Comparative Tracking Index (CTI):			0		Dimensional Stability (%):			-
High-Voltage Arc Tracking Rate (HVTR):			1		High Volt, Low Current Arc Resis (D495):			1
Dielectric Strength (kV/mm):			-		Volume Resistivity (10 ^x ohm-cm):			16

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1998-02-25

Last Revised: 2005-12-14

Underwriters Laboratories Inc®

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness Tested (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	0.8	HB75 (ALL)
			1.5	HB75 (ALL)
			3.0	HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	0.8	650
			1.5	650
			3.0	650
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	0.8	675
			1.5	675
			3.0	675
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-

Underwriters Laboratories Inc®